

Toshiba B-EV4T Desktop Label Printer



SPECIFICATIONS

Printing Technology	Thermal transfer, Direct thermal
Thermal Print Head Type	Flat
Interface	Serial, Parallel, Ethernet 10/100 BaseT, USB 2.0, SD-Card
Memory	4 MB (Flash ROM), 8 MB (S-RAM)
Alignment Base	Central
Media loading	Top opening
Sensor	Reflective, Transmissive
User Interface	Status indicator
Operator keys	Feed
Dimensions (W x D x H)	198 x 258 x 173 mm
Weight	2.4 kg
Duty Cycle	1,000 labels / day

PRINT

Print width	4.25 inches (108 mm), 4.16 inches (105.7 mm)
Print Speed	Up to 5 ips (127 mm/sec), Up to 4 ips (101.6 mm/sec)
Resolution	203 dpi, 300 dpi
Fonts	Bitmap
Print length	Max. 995 mm (203 dpi), Max. 453.2 mm (300 dpi)
Barcodes	EAN8, EAN13, UPC-A, UPC-E, NW-7, CODE 39, CODE 93, ITF, MSI, CODE128, EAN128, Industrial 2 of 5, POSTNET, RM4SCC, KIX CODE, RSS14, PLESSEY
2D Codes	Data Matrix, PDF417, QR Code, Maxi Code, Micro PDF417

MEDIA

Media width	22.4 - 112 mm
Media thickness	0.06 - 0.19 mm
Max outer roller diameter	127 mm, 214 mm*
Core diameter	25.4 - 38.1 mm, 76.2 mm*

RIBBON

Max ribbon roll diameter	40 mm
Standard ribbon length	110 m
Ribbon width	33.8 - 110 mm

FUNCTIONS

Print Functions	ZPL, EPL, DPL, IPL Emulation
Programming language	TPCL, BCI
Issue mode	Batch, Auto cut*, Peel-off*
System Features	BarTender UltraLite