

## Toshiba B-SA4T Ind. Label Printer



### SPECIFICATIONS

Printing Technology	Thermal transfer, Direct thermal
Thermal Print Head Type	Flat
Interface	Parallel, Ethernet 10/100 BaseT, USB 2.0
Memory	16 MB (Flash ROM), 16 MB (SD-RAM)
Alignment Base	Central
Media loading	Top opening
Sensor	Reflective, Transmissive
User Interface	LCD screen (16 characters x 2 lines), Status indicator
Operator keys	Feed, Restart, Pause
Dimensions (W x D x H)	238 x 402 x 332 mm
Weight	15 kg
Duty Cycle	5,000 labels / day

### PRINT

Print width	4.09 inches (104 mm), 4.16 inches (105.7 mm)
Print Speed	Up to 6 ips (152.4 mm/sec)
Resolution	203 dpi, 300 dpi
Fonts	Bitmap, Outline, Writable characters, Optional True Type
Print length	Max. 997 mm
Barcodes	EAN8, EAN13, JAN8, JAN13, UPC-A, UPC-E, NW-7, CODE 39, CODE 93, ITF, MSI, CODE128, EAN128, Industrial 2 of 5, CustomerBarcode, POSTNET, RM4SCC, KIX CODE, RSS14, GTIN, High Priority Customer Barcode
2D Codes	Data Matrix, PDF417, QR Code, Maxi Code, Micro PDF417, CP Code

### MEDIA

Media width	22 - 118 mm
Media thickness	0.08 - 0.17 mm
Max outer roller diameter	200 mm
Core diameter	38 mm, 40 mm, 42 mm, 76.2 mm
Media type	Vellum paper and labels, Matt coated paper, Glossy coated paper, Synthetic film, PET film, Polyimide

### RIBBON

Max ribbon roll diameter	75 mm
Standard ribbon length	450 m
Ribbon width	60 - 110 mm

### FUNCTIONS

Print Functions	Z Mode ready
Programming language	TPCL, BCI
Issue mode	Batch, Auto cut*, Peel-off*
System Features	Double Engine Ribbon Tension Control, Snap-in Print Head, SNMP tool for network management, BarTender UltraLite, Cover damper