

## a\*pos LV-2200E



### SPECIFICATIONS

Printing method	Thermal receipt/ thermal transfer printing
Resolution	203 DPI / 300 DPI
Max print width	Max print width: 203 DPI/ 300 DPI
Max print speed	125mm/s / 75mm/s
Memory	SDRAM :2MB FLASH:1/4/8MB
Interface	RS-232; Parallel port ; USB etc
Physical Dimension	300MM(L)*252MM(W)*190MM(H)
Paper roll size	Internal :25*118mm External: 118*127mm
Operation button	Three push button, three LED indicators
Sensors	Removeble reflective sensor, transmissive sensor , reflective sensor
Operating environment	5°C ~ 45°C, 20% ~90% (40°C)
Store environment	-40°C~ 60°C, 20% ~ 93%(40°C)
Internal font	8 alpha-numeric bitmap fonts
Barcode Type	Code 39, Code 93, Code128 ,Code 2 of 5, Code 11, Code 4, Codeba/New, UPC/EAN/JAN, MSI-Plessey, ISBN/ISSN, UUPC-E, China Post Code, Data Matrix, PDF 417, Maxicode, QR code ,Aztec
Font& barcode rotation	Font& barcode rotation 0,90,180,270 degree
Power	110-240 V switching power supply