

a*pos TRP Receipt Printer



SPECIFICATIONS

Printing Mode	Line Thermal Printing
Printing Density	576 dots/line or 512 dots/line
Printing Speed	260mm/sec.
Printing Width	79.5± 0.5mm, paper external diameter 83mm(Max)
Paper Thickness	0.06~0.08mm
Character Size	ANK Character, Font A: 12x24 dots; Font B: 9x17 dots; Simplified/Traditional Chinese: 24*24dots
Barcode Type	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128
Print Command	ESC/POS Command Compatible
Support Interface	RS232 Serial/Parallel/ USB/ Ethernet/ RS232 Serial+USB
Paper Solve Method	Half Cutting / Whole Cutting
Life of Printer Head	100 km
Adapter Voltage Input	AC110V / 220V. 50~60Hz
Adapter Voltage Output	DC24V / 2.5A
Printer Voltage Input	DC24V / 2.5A
Cash Drawer Control	DC12-24V/1A
Input Buffer	128k bytes
NV Flash Buffer Size	256k bytes
Working Environment	Temperature (0~45° c) Humidity(10~80%)
Storage Environment	Temperature (-10~60° c) Humidity(10~90%)
Operating System	Win 9X / Win ME / Win 2000 / Win 2003 / Win NT / Win XP / Win Vista / Win 7
Weight	1.78kg
Dimension	198x148x138mm